



點序科技股份有限公司  
ASolid Technology Co., Ltd.

3-TH-070

# Datasheet: Industrial SD Memory Card Controller AS2703EN-DI

---

Version 01.00

Document Control Center

2019/1/18

**ASOLID TECHNOLOGY CO., LTD.**

7F.-1, No.83, Sec. 2, Gongdao 5th Rd., Hsinchu 300, Taiwan (R.O.C.)

Tel: +886-3-573-6032

Fax: +886-3-573-6300

## Contents

1. Foreword.....	3
2. Statement of Scope .....	4
3. General Description .....	4
3.1. Feature.....	5
3.2. AS2703EN-DI Function Block Diagram.....	7

ASOLID Confidential

## 1. Foreword

This document has been produced by ASolid Technology Co., Ltd., should the company modifies the contents of this specification, it will be re-released with an identifying change of release date and an increase in revision number as follows:

Revision mn.xy, where:

- mn the first two digit are incremented for major changes of substance, e.g., functional changes.
- xy the second two digits are incremented when minor changes have been incorporated into the specification, i.e., enhancements, corrections, updates, etc.

ASolid Confidential

## 2. Statement of Scope

This Data Book describes the main features and the applications of Industrial SD Memory Card Controller AS2703EN-DI. For more details, please contact [service.asolid@asolid-tek.com](mailto:service.asolid@asolid-tek.com) directly.

ASolid Confidential

### 3. General Description

Industrial SD Memory Card Controller AS2703EN-DI is the SD controller launched by ASolid Technology Co., Ltd., which utilizes UMC process technology. AS2703EN-DI is featured with higher performance and lower power consumption, and supports SD1.0, SD1.01, SD1.10, SD2.00, SD3.00, SD3.01, SD4.00, SD4.10, SD4.20, SD5.00, SD5.10 and SD6.10. The product is built in with single channel high speed flash interface with BCH error correction code, supports all kinds of 2D and 3D NAND type flash including TLC, MLC and SLC.

#### 3.1. Feature

- Fully compatible with SD Card standard specification v1.0/ v1.01/ v1.1/ v2.00/ v3.00/ v3.01/ v4.00/ v4.10/ v4.20/ v5.00/ v5.10/ v6.10.
  - Support SPI mode.
  - Support Bus Speed Mode: Default Speed mode, High Speed mode, SDR12, SDR25, SDR50, SDR104 and DDR50.
  - Supports video speed class specification
  - Supports application performance class specification
  - Copyright Protection Mechanism-Complies with highest security of SDMI standard.
  - Support standard capacity SD memory card ( $\leq 2\text{GB}$ ).
  - Support SDHC capacity (4GB to 32GB).
  - Support SDXC capacity (32GB to 2TB).
  - Support SD command class 0, 2, 4, 5, 6, 7, 8 and 10.
  - Support password protection and built-in write protection features.
- SD card interface with programmable output drive capability
- Flash interface support:
  - UP to 8 flash chip selection and 8-bit flash IO access
  - Support both 1.8V and 3.3V flash for SD card
- Flash memory support:
  - Support ECC function to correct up to 7x-bits data errors per 1K bytes data automatically
  - Support 2D and 3D SLC/MLC/TLC NAND type flash
  - Support flash with 2KB/4KB/8KB/16KB page architecture
  - Support four-plane operation

- Support Toggle Mode flash
- Support ONFI3.0/ONFI2.3/ONFI2.2/ONFI2.1/ONFI2.0 flash
- Low power consumption
- Enhanced ESD design
- Non-Direct remap architecture
- Manufacturing utility ready
- Support industrial grade operating temperature: -40°C to +85°C
- Support die and LGA46 package:
  - Die: AS2703ENLT-DI

ASolid Confidential

### 3.2. AS2703EN-DI Function Block Diagram

The following diagram is the internal block diagram of AS2703EN-DI.




Figure 3-1 AS2703EN-DI Function Block Diagram